

INSTRUCTIONS



MODEL : HONDA CB 500X 13+

PRODUCT : REAR HUGGER Large

CODE : RH-HCB500X13L

CONTENTS

ABS Plastic Wing
2pcs. M6x15 Bolts
2pcs. M6x20 Bolts

MATERIAL SPECIFICATIONS

The product's material, made of **ABS** plastic with acrylic exterior layer, can be placed on your bike without requiring painting but if you want it painted, all paint companies have equivalent machinery at their disposal. If you want to paint it yourself, you should contact them to inform you on what you will need and how to do it.



Photo No 1



Photo No 2



Photo No 3



Photo No 4



Photo No 5



Photo No 6

Placement

OUR COMPANY SUGGESTS THE INSTALLATION BE CARRIED OUT AT A WORKSHOP OR BY QUALIFIED STAFF

- Clean the area around the swingarm.
- Remove the left foot peg and the chain guard (Photo No 1). Then remove the plate holding the rear brake tube.
- Place the fender in position (Photo No 3) – diagonally – in order to avoid damaging the surface.
- Screw the left side of the fender on the old chain guard's position, and then the right side above the plates holding the rear brake tube (Photo No 4 & 5). You may change the old bolts with the new ones included in the fitting kit.
- Before tightening the bolts, make sure the fender is in the right position – centered above the rear wheel.